## **CONDITION REPORT - ELECTRIC**

Manufacturer	Model	Year	Serial Number		
HYSTER COMPANY	E50XN	2014	A268N12401M		
			100-0		
Mast			Hours	10072	
Mast Height Lowered	83		Voltage	48 Volt	
Mast Height Raised	189		Attachment		
Hydraulic Control Valve	3-Function		Directional Control	Monotrol	
Capacity			Tires		
Mast Condition			Steering Pump Condition		
Mast Comments			Steering Pump Comments		
Lift Cylinder Condition			Hydraulic Pump Condition		
Lift Cylinder Comments			Hydraulic Pump Comments		
Tilt Cylinder Condition			Hydraulic Motor Condition		
Tilt Cylinder Comments			Hydraulic Motor Comments		
Carriage Condition			Control System Condition		
Carriage Comments			Control System Comments		
Load Backrest Condition			,		
Load Backrest Comments			Drive Motor Condition		
Forks Condition			Drive Motor Comments		
Forks Comments			Differential Condition		
			Differential Comments		
Overhead Guard Condition			Drive Tires % Remaining	60	
Overhead Guard Comments			Drive Tires Condition		
Overmoda Gadra Cerminente			Steer Tires % Remaining	60	
Seat Condition			Steer Tires Condition	00	
Seat Comments			Steer Axle Condition		
ocal comments			Steer Axle Comments		
General Appearance Condition			Brakes Condition		
General Appearance Comments			Brakes Comments		
General Appearance Comments			biakes Comments		
General Comments			Battery Present	Yes	
			Charger Present	No	
			Electrical Condition		
			Electrical Comments		
The state of the s			1		

Inspector Company Name	PAPE MATERIAL HANDLING	Inspection Date	10/14/2019 1:41:41 PM	
Inspector Name	Derick Guzman			



ained Operators and Mechanics Only



Read Operating Manual located on seat or in operators compartment

Failure to follow operating, inspection, and maintenance instructions can cause serious injury or death! CAPACITY WITH MAST

VERTICAL AND EQUIPPED AS SHOWN



Lift Truck Model E50XN-33

Serial No. A268N12401M

Attachment: 978 mm (39 in) SS Crg + 1067 mm (42 in) Forks

Type E 48 Volts Truck Wt. Less Battery 3020 kg (6660 lb) Truck Wt. Max Battery 4800 kg (10570 lb) Max A.H.(6 Hr Rt)1300 Allowable Battery Wt. 1310 kg (2900 lb) to 1770 kg (3900 lb)

Tread Width 890 mm (35.2 in) Back Till 5 Degrees

Tire Size Front

21X7X15 Cushion

Rear

16X5X10.5 Cushion

Pressure	MUN	Load Height	Dim. B	Center Dim. C	
CAPACITY	Dim. A	610 mm	610 mm		
2110 kg (4650 lb)	4800mm (189 in)	(24 in)	(24 in)		
	4350 mm	610 mm	610 mm		
2180 kg (4800 lb)		(171.3 in)	(24 in)	(24 in)	







