

CONDITION REPORT - ELECTRIC

Manufacturer	Model	Year	Serial Number	Corrected
HYSTER COMPANY	E40XN	2017	A269N03360R	A269N03360R

Mast	3 Stage FFL (Triplex)	Hours	14740
Mast Height Lowered	82	Voltage	36 Volt
Mast Height Raised	187	Attachment	Carton Clamp
Hydraulic Control Valve	4-Function	Directional Control	Monotrol
Capacity	4000	Tires	Cushion

Mast Condition		Steering Pump Condition	
Mast Comments		Steering Pump Comments	
Lift Cylinder Condition		Hydraulic Pump Condition	
Lift Cylinder Comments		Hydraulic Pump Comments	
Tilt Cylinder Condition		Hydraulic Motor Condition	
Tilt Cylinder Comments		Hydraulic Motor Comments	
Carriage Condition		Control System Condition	
Carriage Comments		Control System Comments	
Load Backrest Condition		Drive Motor Condition	
Load Backrest Comments		Drive Motor Comments	
Forks Condition		Differential Condition	
Forks Comments		Differential Comments	
Overhead Guard Condition		Drive Tires % Remaining	
Overhead Guard Comments		Drive Tires Condition	Chunked
Seat Condition	Damaged	Steer Tires % Remaining	70%
Seat Comments	torn	Steer Tires Condition	
General Appearance Condition	Fair	Steer Axle Condition	
General Appearance Comments	Impact damage	Steer Axle Comments	
		Brakes Condition	
		Brakes Comments	

General Comments

right hand header hoses chaffed, main lift hose chaffed, play in control valve linkage, fourth function plastic taped together, trunion bushings worn, clamp bushings worn, clamp cylinders drift apart, freelif chains worn out, battery dirty, steer pins and bushings worn, steer wheel bearings need to be repacked

Battery Present	Yes
Charger Present	Yes
Electrical Condition	
Electrical Comments	

Inspector Company Name	Eastern Lift Truck	Inspection Date	2/8/2023 10:16:06 AM
Inspector Name	jpellini		

(* Legend: =Checked OK)



















WARNING

Operators and Mechanics Only

Read Operating Manual located on seat or in operators compartment

Failure to follow operating, location, and maintenance instructions can cause injury or death.

CAPACITY WITH MAST VERTICAL AND EQUIPPED AS SHOWN



Lull Truck Model **E40XN**

Serial No. **A269N03360R**

Attachment: **907 mm (36 in) Carriage + Carton Clamp Long Reach LCC35NSB5448STD0AQ**

Truck Wt. Less Battery **3350 kg (7390 lb)** Type **36 Volts**

Truck Wt. Max Battery **4490 kg (9890 lb)** Max A.H. (6 Hr Rt) **1200**

Allowable Battery Wt. **840 kg (1850 lb) to 1130 kg (2500 lb)**

Tread Width **808 mm (31.8 in)** Back Tilt **5.0 Degrees**

Tire: Front Rear

Size: **18X7X12-1/8 Cushion** **15X5X11-1/4 Cushion**

Pressure: --- ---

MAXIMUM CAPACITY	Load Height Dim. A	Load Center	
		Dim. B	Dim. C
120 kg (250 lb)	4750 mm (156.2 in)	610 mm (24 in)	610 mm (24 in)
1240 kg (2750 lb)	2900 mm (114.2 in)	610 mm (24 in)	610 mm (24 in)





