

# CONDITION REPORT - ELECTRIC

Manufacturer	Model	Year	Serial Number
HYSTER COMPANY	E50XN	2014	A268N12388M

Mast		Hours	8159
Mast Height Lowered	83	Voltage	48 Volt
Mast Height Raised	189	Attachment	
Hydraulic Control Valve Capacity	3-Function	Directional Control	Monotrol
		Tires	

Mast Condition	Steering Pump Condition	
Mast Comments	Steering Pump Comments	
Lift Cylinder Condition	Hydraulic Pump Condition	
Lift Cylinder Comments	Hydraulic Pump Comments	
Tilt Cylinder Condition	Hydraulic Motor Condition	
Tilt Cylinder Comments	Hydraulic Motor Comments	
Carriage Condition	Control System Condition	
Carriage Comments	Control System Comments	
Load Backrest Condition		
Load Backrest Comments	Drive Motor Condition	
Forks Condition	Drive Motor Comments	
Forks Comments	Differential Condition	
	Differential Comments	
Overhead Guard Condition	Drive Tires % Remaining	60
Overhead Guard Comments	Drive Tires Condition	
	Steer Tires % Remaining	60
Seat Condition	Steer Tires Condition	
Seat Comments	Steer Axle Condition	
	Steer Axle Comments	
General Appearance Condition	Brakes Condition	
General Appearance Comments	Brakes Comments	

General Comments

Battery Present	Yes
Charger Present	No
Electrical Condition	
Electrical Comments	

Inspector Company Name	PAPE MATERIAL HANDLING	Inspection Date	10/14/2019 1:35:52 PM
Inspector Name	Derick Guzman		

(\* Legend: =Checked OK)

**WARNING**

ned Operators and  
Mechanics Only

Read Operating  
Manual located on  
seat or in  
operators  
compartment

Failure to follow op  
eration, and ma  
instructions can ca  
serious injury or de

CAPACITY WITH  
VERTICAL AN  
EQUIPPED AS



Lift Truck Model

Serial No. A268N12388M

Attachment: 978 mm (39 in) SS Crg + 1067 mm (42 in) Forks

Truck Wt. Less Battery 3020 kg (6660 lb) Type E 48 Volts  
Truck Wt. Max Battery 4800 kg (10570 lb) Max A.H.(6 Hr Rt)1300  
Allowable Battery Wt. 1310 kg (2900 lb) to 1770 kg (3900 lb)  
Tread Width 890 mm (35.2 in) Back Tilt 5 Degrees

Tire Front Rear

**NOTICE TO USER**

The U.S.A. Occupational Safety and Health  
Act of 1970 and other national safety codes  
require a new plate if this unit is equipped  
other than stated on plate. Obtain the correct  
plate from your authorized dealer.

1335137.06

To remove pull here



14751433







