

# CONDITION REPORT - ELECTRIC

<b>Manufacturer</b>	<b>Model</b>	<b>Year</b>	<b>Serial Number</b>
<b>YALE MANUFACTURER</b>	<b>NR045EB</b>	<b>2018</b>	<b>D861N05188S</b>

Mast	3 Stage FFL (Triplex)	Hours	6578
Mast Height Lowered	131	Voltage	36 Volt
Mast Height Raised	302	Attachment	
Hydraulic Control Valve	3-Function	Directional Control	Lever
Capacity	4500	Tires	Cushion

Mast Condition	Inspected	Steering Pump Condition	Inspected
Mast Comments		Steering Pump Comments	
Lift Cylinder Condition	Inspected	Hydraulic Pump Condition	Inspected
Lift Cylinder Comments		Hydraulic Pump Comments	
Tilt Cylinder Condition	Inspected	Hydraulic Motor Condition	Inspected
Tilt Cylinder Comments		Hydraulic Motor Comments	
Carriage Condition	Inspected	Control System Condition	Inspected
Carriage Comments		Control System Comments	
Load Backrest Condition	Inspected	Drive Motor Condition	Inspected
Load Backrest Comments		Drive Motor Comments	
Forks Condition	Inspected	Differential Condition	
Forks Comments		Differential Comments	
Overhead Guard Condition	Inspected	Drive Tires % Remaining	50
Overhead Guard Comments		Drive Tires Condition	Inspected
Seat Condition		Steer Tires % Remaining	
Seat Comments		Steer Tires Condition	Not-Selected
General Appearance Condition	Good	Steer Axle Condition	Inspected
General Appearance Comments		Steer Axle Comments	
General Comments		Brakes Condition	Inspected
		Brakes Comments	

Battery Present	Yes
Charger Present	Yes
Electrical Condition	Inspected
Electrical Comments	

Inspector Company Name	Inspection Date	7/5/2023 10:20:09 AM
Inspector Name	jlew	

(\* Legend: =Checked OK)  
Inspected

**WARNING**

**Trained Operators and Mechanics Only**



Read Operating Manual located on or near seat.

Be sure to follow operating, inspection and maintenance instructions. Can cause serious injury or death!

**Yale**

Model NR045EBNS36TE131  
Serial Number D861N(5)188S

Attachment Forks 1187 mm (47 in) ISS Carriage 1967 mm (77 in)

Type EO 3.36 Volts Max.A.H. 1240  
Truck Weight Less Battery 2980 kg (6570 lb)  
Truck Weight Max.Battery 4050 kg (8920 lb)

Allowable battery weight 840 kg (1860 lb) to 1070 kg (2350 lb)


Base Width 1149 mm (45.3 in)

Wheel Base 1457 mm (57.4 in)



132271877

MAXIMUM CAPACITY	Load Height	Load Center		
		Dim. A	Dim. B	Dim. D
1460 kg (3200 lb)	7650 mm (302 in)	110 mm (4.3 in)	510 mm (20 in)	1100 mm (43 in)
2040 kg (4500 lb)	4900 mm (193 in)	110 mm (4.3 in)	610 mm (24 in)	1100 mm (43 in)







**Yale**   
iSi Technology™

0.0mph 4  
6578h



SERIAL NUMBER / NÚMERO DE SERIE / N°



RSH105863

© 2008 U.S.A. P&O DE DIESEL S.A. P&O S'INDUSTRIE S.A.

911000

TIP	E1250-13
CAPACITAT / CAPACITÉ	750 Ah @ 20°C
VELOCITAT DE CARGA / VELOCITAT DE LA CARGA	MIN. 30.0 A MAX. 37.5 A
VELOCITAT DE CARGA GRAVITACIONAL / VELOCITAT DE CARGA GRAVITACIONAL	1.280



