

# CONDITION REPORT - ELECTRIC

<b>Manufacturer</b>	<b>Model</b>	<b>Year</b>	<b>Serial Number</b>
YALE MANUFACTURER	MPB045VG	2018	A245N18438S

Mast	Hours	618
Mast Height Lowered	Voltage	
Mast Height Raised	Attachment	
Hydraulic Control Valve	Directional Control	
Capacity	Tires	

Mast Condition	Not applicable	Steering Pump Condition	Inspected
Mast Comments		Steering Pump Comments	
Lift Cylinder Condition	Inspected	Hydraulic Pump Condition	Inspected
Lift Cylinder Comments		Hydraulic Pump Comments	
Tilt Cylinder Condition	Not applicable	Hydraulic Motor Condition	Inspected
Tilt Cylinder Comments		Hydraulic Motor Comments	
Carriage Condition	Not applicable	Control System Condition	Inspected
Carriage Comments		Control System Comments	
Load Backrest Condition	Not applicable	Drive Motor Condition	
Load Backrest Comments		Drive Motor Comments	
Forks Condition	Inspected	Differential Condition	Inspected
Forks Comments		Differential Comments	
Overhead Guard Condition	Not applicable	Drive Tires % Remaining	
Overhead Guard Comments		Drive Tires Condition	Inspected
Seat Condition	Not applicable	Steer Tires % Remaining	
Seat Comments		Steer Tires Condition	Not-Selected
		Steer Axle Condition	Not applicable
General Appearance Condition	Fair	Steer Axle Comments	
General Appearance Comments		Brakes Condition	Inspected
		Brakes Comments	

General Comments	Battery Present	Yes
Solid Unit	Charger Present	
	Electrical Condition	Inspected
	Electrical Comments	

Inspector Company Name	Inspection Date
Inspector Name	



**WARNING**  
Trained Operators and  
Mechanics Only

**Yale**

L8E Truck Model  
MPD045VGN24T2640  
Serial Number A265N184385  
Battery Type E 24 Volt Max A.T. 440

Read Operating  
Manual located behind  
cover with cover 90  
degrees to cover

Truck Weight Less Battery 370 kg (810 lbs)  
Truck Weight Max Battery 450 kg (990 lbs)  
Maximum Battery Weight 26 kg (58 lbs)  
Maximum Battery Weight 175 kg (385 lbs)

If safety or health hazard exists,  
disconnect, with proper  
protection, and discharge  
battery and cables before  
working on them.

**RECHARGE CAPACITY**  
2040 Ah (20hr) @ 25°C (77°F)  
See full and correct weight distribution  
Table E on other truck  
See 9020





