

CONDITION REPORT - ELECTRIC

Manufacturer	Model	Year	Serial Number	Corrected
YALE MANUFACTURER	NR045EB	2013	D861N01826M	D861N01826M

Mast	3 Stage FFL (Triplex)	Hours	7665
Mast Height Lowered	125	Voltage	36 Volt
Mast Height Raised	287	Attachment	Side Shifter
Hydraulic Control Valve	3-Function	Directional Control	Lever
Capacity	4500	Tires	Cushion

Mast Condition	Kicking / Rough movement	Steering Pump Condition	
Mast Comments		Steering Pump Comments	
Lift Cylinder Condition		Hydraulic Pump Condition	
Lift Cylinder Comments		Hydraulic Pump Comments	
Tilt Cylinder Condition		Hydraulic Motor Condition	
Tilt Cylinder Comments		Hydraulic Motor Comments	
Carriage Condition	Tight / loose	Control System Condition	
Carriage Comments		Control System Comments	
Load Backrest Condition		Drive Motor Condition	
Load Backrest Comments		Drive Motor Comments	
Forks Condition		Differential Condition	
Forks Comments		Differential Comments	
Overhead Guard Condition		Drive Tires % Remaining	50
Overhead Guard Comments		Drive Tires Condition	
Seat Condition		Steer Tires % Remaining	50
Seat Comments		Steer Tires Condition	Not-Selected
General Appearance Condition	Good	Steer Axle Condition	
General Appearance Comments	Impact damage	Steer Axle Comments	
		Brakes Condition	
		Brakes Comments	

General Comments

Mast makes loud noise when passing free-lift. Plastic broken in operator compartment by the hour meter.

Battery Present	Yes
Charger Present	Yes
Electrical Condition	
Electrical Comments	

Inspector Company Name	Briggs Equipment	Inspection Date	10/9/2019 12:55:29 PM
Inspector Name	jschell		

(* Legend: =Checked OK)

Yale

Lift Truck Model NR045EBNS36TE125

Serial No. D861N01826M

Attachment: 787 mm (31 in) SS Crg + 1067 mm (42 in) Forks

Truck Wt. Less Battery 2948 kg (6500 lb) Type EO 36 Volts
Truck Wt. Max Battery 4014 kg (8850 lb) Max A.H (6 Hr. Rt) 1240
Allowable Battery Wt. 840 kg (1850 lb) to 1060 kg (2350 lb)
Base Width 1320 mm (52.25 in)
Wheel Base 1450 mm (57.4 in)

MAXIMUM CAPACITY	Load Height Dim. A	Load Center	
		Dim. B	Dim. C
1700 kg (3750 lb)	7290mm (287 in)	610 mm (24 in)	610 mm (24 in)
2040 kg (4500 lb)	4790 mm (188.6 in)	610 mm (24 in)	610 mm (24 in)















