

CONDITION REPORT - ELECTRIC

Manufacturer	Model	Year	Serial Number
HYSTER COMPANY	N35ZR2	2015	E470N01893N

Mast	3 Stage FFL (Triplex)	Hours	8411
Mast Height Lowered	119	Voltage	36 Volt
Mast Height Raised	272	Attachment	
Hydraulic Control Valve	3-Function	Directional Control	Lever
Capacity	3500	Tires	Cushion

Mast Condition		Steering Pump Condition	
Mast Comments		Steering Pump Comments	
Lift Cylinder Condition		Hydraulic Pump Condition	
Lift Cylinder Comments		Hydraulic Pump Comments	
Tilt Cylinder Condition		Hydraulic Motor Condition	
Tilt Cylinder Comments		Hydraulic Motor Comments	
Carriage Condition		Control System Condition	
Carriage Comments		Control System Comments	
Load Backrest Condition			
Load Backrest Comments		Drive Motor Condition	
Forks Condition		Drive Motor Comments	
Forks Comments		Differential Condition	
		Differential Comments	
Overhead Guard Condition		Drive Tires % Remaining	60
Overhead Guard Comments		Drive Tires Condition	
		Steer Tires % Remaining	70
Seat Condition		Steer Tires Condition	
Seat Comments		Steer Axle Condition	
		Steer Axle Comments	
General Appearance Condition		Brakes Condition	
General Appearance Comments		Brakes Comments	
General Comments		Battery Present	Yes
		Charger Present	No
		Electrical Condition	
		Electrical Comments	

Inspector Company Name	MH EQUIPMENT	Inspection Date	7/2/2019 10:06:00 AM
Inspector Name	Jmarzian		

(* Legend: =Checked OK)

WARNING

Trained Operators and Mechanics Only



Read Operating Manual located on seat or in operators compartment

Failure to follow operating, inspection, and maintenance instructions can cause serious injury or death!

CAPACITY WITH MAST VERTICAL AND EQUIPPED AS SHOWN



L/R Truck Model N3529C2-16.5

Serial No. E-470W01893N

Attachment: 767 mm (31 in) SS Crg + 1067 mm (42 in) Forks

Truck Wt. Less Battery 2543 kg (5652 lb) Type EO 36 Volts

Truck Wt. Max Battery 2629 kg (5802 lb) Max A.H. (5 Hr R) 1240

Allowable Battery Wt. 829 kg (1850 lb) to 1,066 kg (2350 lb)

Base Width 1150 mm (45.25 in)

Wheel Base 1450 mm (57.4 in)

MAXIMUM CAPACITY	Load Height Dim. A	Load Center	
		Dim. B	Dim. C
1275 kg (2800 lb)	6000mm (272 in)	610 mm (24 in)	610 mm (24 in)
1590 kg (3500 lb)	6250 mm (246.4 in)	610 mm (24 in)	610 mm (24 in)



39.305983 -84.474308
7/1/2019 10:21:44 AM



39.305983 -84.474308
7/1/2019 10:20:02 AM



39.305983 -84.474308
7/1/2019 10:19:47 AM



39.305983 -84.474308
7/1/2019 10:19:34 AM



39.305983 -84.474308
7/1/2019 10:19:20 AM

WARNING

Only Trained Operators and Mechanics Only

Read Operating Manual located on seat or in operator's compartment.

Improper operation and maintenance can cause injury or death.



Lift Truck Model **N35ZR2-16.5**

Serial No. **E470N01893N**

Attachment: **787 mm (31 in) SS Crg + 1067 mm (42 in) Forks**

Truck Wt. Less Battery **2563 kg (5652 lb)** Type **EO 36 Volts**

Truck Wt. Max Battery **3629 kg (8002 lb)** Max A.H. (6 Hr Ft) **124**

Allowable Battery Wt. **839 kg (1850 lb) to 1,066 kg (2350 lb)**

Base Width **1150 mm (45.25 in)**

Wheel Base **1450 mm (57.4 in)**

MAXIMUM CAPACITY	Load Height Dim. A	Load Center	
		Dim. B	Dim. C
1270 kg			

