CONDITION REPORT - ELECTRIC

Manufacturer	Model	Year	Serial Number	
HYSTER COMPANY	R30XM3	2017	H118N04271R	
Mast	3 Stage FFL (Triplex)		Hours	6833 Inspected
Mast Height Lowered			Voltage	36 Volt
Mast Height Raised	213		Attachment	None
Hydraulic Control Valve	3-Function		Directional Control	Lever
Capacity	3000		Tires	Cushion
Mast Condition			Chapting Dump Condition	
	Inspected		Steering Pump Condition	Inspected
Mast Comments			Steering Pump Comments	
Lift Cylinder Condition	Inspected		Hydraulic Pump Condition	
Lift Cylinder Comments			Hydraulic Pump Comments	
Tilt Cylinder Condition	Inspected		Hydraulic Motor Condition	
Tilt Cylinder Comments			Hydraulic Motor Comments	
Carriage Condition	Inspected		Control System Condition	Inspected
Carriage Comments	-		Control System Comments	
Load Backrest Condition	Inspected			
Load Backrest Comments	1		Drive Motor Condition	Inspected
Forks Condition	Inspected		Drive Motor Comments	mepeetea
Forks Comments	inspected		Differential Condition	Inspected
			Differential Comments	Inspected
Overhead Guard Condition	Increated		Drive Tires % Remaining	70
Overhead Guard Comments	Inspected		Drive Tires Condition	
Overhead Odard Comments			Steer Tires % Remaining	70
Seat Condition	.		Steer Tires Condition	10
	Inspected			
Seat Comments			Steer Axle Condition	
			Steer Axle Comments	
General Appearance Condition	Good		Brakes Condition	
General Appearance Comments			Brakes Comments	
General Comments			Battery Present	Yes
			Charger Present	No
			Electrical Condition	Inspected
			Electrical Comments	mspected
Inspector Company Name	T = 1/		Inspection Date	8/9/2023 3:58:21 PM
Inspector Name	Tgraf			





Lift Truck Model R30XM3

Attachment 1016 mm (40 in) Wide X 698 mm (27.5 in) Deep Op Platform + 1067 mm (42 in) Forks

- Max A.H. (6 Hr Rt) 1020

Min Battery VI. 771 kg (1700 lb) Max Battery VI. 771 kg (1700 lb) Max Battery VI. 998 kg (2200 lb) Batter Virdith 1041 mm (41 in) Witheribase 14BB mm (00.00 in)

Trained Operators and Mechanics Only



Read Operating Manual lo on Unive Unit Gover

WARNING

Failure to follow operating, inspection, and maintenance instructions can cause serious

CAPACITY WITH MAST VERTICAL AND EQUIPPED AS SHOWN

MAXIMUM	1360 kg (3000 lb)	0 kg (0 lb)
Load Height	5410 mm (213 in)	0 mm (0 in)
Load Center	610 mm (24 in)	0 mm (0 in)
Dim.B	610 mm	0 mm (0 in)





