

# CONDITION REPORT - ELECTRIC

Manufacturer	Model	Year	Serial Number
HYSTER COMPANY	E50XN	2014	A268N12211M

Mast	Hours	4916
Mast Height Lowered	Voltage	36 Volt
Mast Height Raised	Attachment	
Hydraulic Control Valve	Directional Control	Lever
Capacity	Tires	

Mast Condition	Steering Pump Condition
Mast Comments	Steering Pump Comments
Lift Cylinder Condition	Hydraulic Pump Condition
Lift Cylinder Comments	Hydraulic Pump Comments
Tilt Cylinder Condition	Hydraulic Motor Condition
Tilt Cylinder Comments	Hydraulic Motor Comments
Carriage Condition	Control System Condition
Carriage Comments	Control System Comments
Load Backrest Condition	Drive Motor Condition
Load Backrest Comments	Drive Motor Comments
Forks Condition	Differential Condition
Forks Comments	Differential Comments
Overhead Guard Condition	Drive Tires % Remaining
Overhead Guard Comments	Drive Tires Condition
Seat Condition	Steer Tires % Remaining
Seat Comments	Steer Tires Condition
General Appearance Condition	Steer Axle Condition
General Appearance Comments	Steer Axle Comments
	Brakes Condition
	Brakes Comments

Damaged  
RIPPED - TAPED

Rust

Battery Present	Yes
Charger Present	
Electrical Condition	
Electrical Comments	

General Comments

RIPPED SEAT - TAPED OVEREVERY DAY WEAR - PAINT CORROSION - RUSTED IN SPOTSNO FIRE EXT PRESENT - NOT SURE IF ONE WAS PRESENT AT TIME OF DELIVERY

Inspector Company Name	BRIGGS EQUIPMENT	Inspection Date	6/11/2019 4:40:11 PM
Inspector Name	Christian Dano		

(\* Legend: =Checked OK)







**WARNING**

**Ttrained Operators and Mechanics Only**



Read Operating Manual located on seat or in operators compartment

Failure to follow operating, inspection, and maintenance instructions can cause serious injury or death! CAPACITY WITH MAST VERTICAL AND EQUIPPED AS SHOWN



Lift Truck Model E50XN-30  
Serial No. A268N12211M

Attachment: 978 mm (39 in) SS Crg + 1067 mm (42 in) Forks

Truck Wt. Less Battery 3200 kg (7050 lb) Type E 36 Volts  
Truck Wt. Max Battery 4800 kg (10560 lb) Max A.H.6 hr RT1500

Allowable Battery Wt. 1130 kg (2500 lb) to 1590 kg (3510 lb)

Tread Width 890 mm (35.2 in) Back Tilt 5 Degrees

Front 21X7X15 Cushion  
Rear 16X5X10.5 Cushion

Pressure ---

MAXIMUM CAPACITY	Load Height	Dim. A	Dim. B	Dim. C	Load Center
2110 kg (4650 lb)	4800mm (189 in)	610 mm (24 in)	610 mm (24 in)	610 mm (24 in)	610 mm (24 in)
2190 kg (4800 lb)	4350 mm (171.3 in)	610 mm (24 in)	610 mm (24 in)	610 mm (24 in)	610 mm (24 in)

















